AS620RF-RC

Télécommande pour AS620RF-TR-N, 868 Mhz.

The AS620RF-RC is a two-way remote control with four programmable buttons to send easy remote commands to the transceiver module AS620RF-TR-N. Immediate visual feedback of the status will be provided by the 4 status LEDs, one for each output.

All the main functions of an alarm control panel can be assigned to the buttons, i.e. switching on, switching off, specific output activations, etc.

Up to 4 remote controls can be added to allow the end-user to operate his security system in a quick and easy way.

Détails

- Commande à distance pour le transcepteur 868Mhz - AS620-TR-N
- Communication sans fil bidirectionnelle
- Fourni avec deux graphismes de boutons différents
- Jusqu'à 4 télécommandes avec un seul transcepteur AS620RF-TR-N
- Voyants d'état

AS620RF-RC

Télécommande pour AS620RF-TR-N, 868 Mhz.

Spécifications techniques

Electrical

Operating voltage	3 VDC lithium battery, model CR2032

Physical

Physical dimensions	80 x 35 x 16 mm

General

Operating frequency	868 MHz
Wireless signal range	200 m
Compatability	AS620RF-TR-N

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web fr.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 12 November 2026 - 18:57