RF581I4

Trådløs røg/varme detektor, til 433-63 standarden

Description

The RF581I4 is a wireless smoke / heat alarms, designed for use in a residential intrusion system with a compatible receiver understanding the legacy 433-63bit protocol.

The device has a test button surrounded by a status LED and a built-in sounder for alarm indication. The status LED flashes red every 45 seconds to indicate normal status (no alarm). When smoke or heat is detected (as configured), the status LED changes from flashing to continuously on, the built-in sounder is activated, and an alarm signal is sent to the control panel.

The test button itself can also be used to silence the internal sounder in case of a low battery alert and is, of course, used when performing a sensitivity and alarm test. The test button can even be used to perform a remote monitoring station alarm test.

The device sends a supervisory signal to the receiver every 15-18 minutes to report its status.

In addition to the above the device also has a tamper switch that triggers a tamper signal transmission when the device is removed from its mounting base and also performs a self-diagnostic monitoring the sensitivity and operation status of the device.

The configuration switch hidden behind the batteries, can be used to select the sounder tone and volume. Another set of switches help to select the smoke and/or heat as well as their associated sensitivity levels.

We also have siting guidelines helping the installer to define where to put these devices in a residential application.



Detaljer

- Option to select one technology only (heat or smoke) or both technologies (heat and smoke)
- Can also be used as a standalone detector
- Built-in sounder
- Test button surrounded with status LED
- 8 selectable sounder tones
- 5 years estimated battery life running on 2 batteries
- 2 additional battery slots available to further extend battery life
- EN14604:2005/AC:2008 and BS 5446-2:2003 certified

RF5811I4

Trådløs røg/varme detektor, til 433-63 standarden

Tekniske specifikationer

General

Type	Wärme, Rauch
Built-in sounder	Yes
Sounder output	85 dBA bei 3 m (Dauerton)
Status LED	Yes

Wired/wireless

Wired-wireless	Drahtlos
Wireless frequency	433-MHz Ältere Version

Electrical

Operating voltage	2.4 to 3.3 VDC
Batteries	2 x 3V CR123A or DL123

Physical

Detector dimensions	109 x 62 mm
Colour	Weiß

Environmental

Vandal proof	Yes
Operating temperature	-10 to 55° C
Storage temperature	0 to 30° C
Relative humidity	Up to 90% non-condensing

Regulatory

Compliancy	CE
Certification	EN14604
Standards	BS5446-2

Kidde Global Solutions er et innovativt selskab og forbeholder sig ret til at ændre produktspecifikationer uden varsel. De nyeste produktspecifikationer kan du finde på dk.firesecurityproducts.com eller ved at kontakte din salgsrepræsentant hos.

Last updated on 12 November 2026 - 18:57