TESTIFIRE-ADAP

XTR2 Adaptor for aspiration and flat detectors

General

The TESTIFIRE-ADAP is a specialist adaptor to replace the standard membrane on a Testifire XTR2 test cup. It enables functional testing of aspirating smoke detection systems. It can also be used to test flat/flush detectors.



Details

- Fits to Testifire XTR2 in place of standard membrane
- Allows placement around ASD pipe and alignment with sampling hole
- Also suitable for use with flat or flush mounted detectors

TESTIFIRE-ADAP

XTR2 Adaptor for aspiration and flat detectors

Technical specifications

Physical

Colour	Schwarz

Environmental

Vandal proof	No
Operating temperature	5 to 45°C (41 to 113°F)
Storage temperature	-10 to 50°C (14 to 122°F)
Relative humidity	0 to 85% non-condensing - operating 0 to 90% non-condensing - storage

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE

SKU info

Product brand	testifire

Compatible products

Category	Reference	Description
Test Equipment	TESTIFIRE-XTR2	All-in-one connected smoke/heat detector test kit
Test Equipment	TESTIFIRE-XTR2-6M	All-in-one connected smoke/heat detector test kit to 6 m
Test Equipment	TESTIFIRE-XTR2-HEAD	All-in-one connected smoke/heat detector test head

EDWARDS
Built for Resilience

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 25 October 2024 - 13:46