# ATS1197

**ATS Smart Card Reader with keypad supplied with 2 m cable**




## Details

- Full epoxy filled weather proof construction
- Keypad

# ATS1197

## ATS Smart Card Reader with keypad supplied with 2 m cable

## Technische specificaties

### System

| | |
|---|---|
| Max. reader distance to panel | 1500 |
| Supported card types | HiTag2 |
| Addressing type | Carte d'adressage, Adressage clavier, Logiciel d'adressage |
| No. of LEDs | 3 LEDs |

### Technology

| | |
|---|---|
| Reader type | Nærhed, Carte à puce |
| Reader operating-transmitting frequency | 125 KHz |
| Supported technology 125 kHz | HiTag 2 |

### Interface & connections

| | |
|---|---|
| Interface | ATS RS-485 |
| Connector type | Svinesvans |
| Pigtail length | 200 |

### Inputs/outputs

| | |
|---|---|
| Inputs | Demande de sortie |
| Outputs | 1 collecteur ouvert (50 mA) |

### Tamper type

| | |
|---|---|
| Pry-off tamper | Yes |

### Operation

| | |
|---|---|
| PIN keypad | Yes |

### Electrical

| | |
|---|---|
| Power supply value | 8.5 to 14 VDC |
| Current consumption | 110<br>40 |

### Physical

| | |
|---|---|
| Physical dimensions | 140 × 121 × 22 mm |
| Colour | Gris foncé |
| Mounting Type | Montage en surface |

### Environmental

| | |
|---|---|
| Operating temperature | -40 to +50°C |
| Environment | Udendørs |
| IP rating | IP66 |

Als een bedrijf van innovatie behoudt Kidde Global Solutions zich het recht voor productspecificaties zonder kennisgeving te wijzigen. Ga voor de nieuwste productspecificaties online naar be.firesecurityproducts.com of neem contact op met uw verkoopvertegenwoordiger.

Last updated on 12 November 2026 - 18:57