AS271

Indoor siren, 1 tone, with flash

Application

The AS270 series of sirens is ideal for use as an internal alarm sounder for residential and industrial alarm applications.



Details

- Low current consumption
- Pry-off & opening tamper protection
- Easy to install (1 fixing screw for cover)
- Vertical or horizontal mounting
- Self activating version available
- ANPI, NFA2P and VdS version available

AS271
Indoor siren, 1 tone, with flash

Technical specifications

General

Accessory group	Sirene
Type	Indendørs sirene
Sounder output (dB @ distance)	101 dB at 1 m (typical)

Flash specifications

Current consumption	110 mA
Light output	100,000 peak lumens
Flash frequency	60 flashes/minute

Electrical

Operating voltage	10 to 14.2 VDC
Current consumption	120 mA at 12 VDC (typical)

Physical

Physical dimensions	155 x 114 x 44 mm
Net weight	240 g
Colour	Hvid
Material	ABS

Environmental

Operating temperature	-25 to +55°C
IP rating	IP31

Regulatory

Certification	CE

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 16 June 2026 - 15:32