DT2063N

2000 Series addressable heat detector with dual alarm LEDs and a remote indicator output



DT2063N

2000 Series addressable heat detector with dual alarm LEDs and a remote indicator output

Spécifications techniques

General

Addressing method	Rotary switch

Electrical

Power supply type	Lus aangedreven

Detection

Monitoring	Alarm threshold
Alarm temperature (typical)	> +40°C

Physical

Colour	Wolkenweiß (RAL 9001)
Mounting type	Deckenmontage
Material (body)	Plastik

Environmental

Vandal proof	No
Application temperature (typical)	+25°C
Environment	Drinnen

Regulatory

Compliancy	CE, REACH, RoHS 3, WEEE
Certification	CPR

Produits compatibles

Catégorie	Référence	Description
Detection device	DB2002	Socle, 100 mm, 4 bornes, pour commande indicateur d'action
Detection device	DB2004	2000 Series deep base, 4 terminals with ground connection - 100 mm
Detection device	DB2016	Socle isolateur
Notification device	AI672	Indicateur d'action lumineux
Notification device	AI673	Indicateur d'action lumineux et sonore
Notification device	DB2368IAS-W	2000 Series sounder base with isolator (white)

KIDDE GLOBAL SOLUTIONS

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 12 November 2026 - 18:57