DMN700E100

Manual Callpoint, Red, 100 Ohm, Free Contact, Outdoor, Surface Mount, Resetable

General

The DMN700E100 is a weather proof MCP, designed for outdoor application with an IP67 ingress protection rating. It comes with snap on connections, which ensure ease of installation and maintenance. Assembly of the unit is also made easy with a simple snap on fit, and 4 screws to secure the unit.

Installation

Installation time and ultimately cost, are of paramount importance. The MCP range directly reflects this need by providing a unique ‘plug and play’ concept designed specifically to reduce installation time. All new MCP products utilise a special terminal block, where all initial installation cabling is terminated. This terminal block is then simply connected to the back of the MCP. Simple,but effective, with no re-termination required and no time wasted.

Options and Approvals

Through new standards and legislation, both glass and re-settable operating elements may be used. To provide the greatest ‘flex-ability’, the new MCP range can be configured as either break glass or re-settable unit by simply changing from one element to another. No other additional parts or alternative products are required. Full compliance with the latest standards is essential and the new MCP outdoor call point range is approved to the latest EN54-11 standard.



Details

- Easy to install
- With break glass or resettable element
- Easy to replace glass
- High quality micro switch
- IP67 rated
- EN54-11 & CPD approved

DMN700E100

Manual Callpoint, Red, 100 Ohm, Free Contact, Outdoor, Surface Mount, Resetable

Technical specifications

General

Status indication	Alarm flag
Compatibility	Conventional alarm systems

Electrical

Cable specification	0.5 to 2.5 mm²
No. of cable cores	2

Detection

Detection principle	Manual activation
Monitoring	Activated, Off
Installation height	Determined by local regulation

Output

Output quantity	2
Output type and rating	2 A @ 30 VDC, resistive load, 100 Ω in series

Isolation

Series resistance	100 Ohm

Physical

Physical dimensions	98 x 94 x 70 mm (W x H x D)
Net weight	270 g
Colour	Czerwony (RAL 3001)
Mounting type	Bagkasse, Montaż nawierzchniowy
Material (body)	PC / ABS
Functional marking	House on fire

Environmental

Vandal proof	No
Operating temperature	-30 to +70°C
Relative humidity	0 to 95% noncondensing
Environment	Udendørs
IP rating	IP67

Regulatory

Compliancy	CE, REACH, RoHS 2, WEEE
Certification	CPR, EN54-11

Compatible products

Category	Reference	Description
Detection device	DMN782	Hinged transparent MCP protection cover
Detection device	DMN787	Surface mounting box with earth connector, red
Detection device	DMN800	Resettable element for Manual Call Point

KIDDE GLOBAL SOLUTIONS

As a company of innovation, Kidde Global Solutions reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 29 January 2025 - 15:35