ATS1190X4

4 pack ATS1190 Smart card reader with 2.5 m cable



ATS1190X4

4 pack ATS1190 Smart card reader with 2.5 m cable

Spécifications techniques

System

Max. reader distance to panel	1500
Supported card types	HiTag2
Addressing type	Indirizzamento tessere, Indirizzamento tastiere, Indirizzamento software
No. of LEDs	Tricolor
No. of covers included	4, White
Reader accessory	Cover colorate opzionali

Technology

Reader type	Nahdistanz, Smartcard
Reader operating-transmitting frequency	125 KHz
Supported technology 125 kHz	HiTag 2

Interface & connections

Interface	ATS RS-485, Wiegand
Connector type	Zopf
Pigtail length	250

Inputs/outputs

Inputs	Richiesta di uscita
Outputs	1 Open Collector (25 mA)

Tamper type

Pry-off tamper	Yes

Operation

PIN keypad	No

Electrical

Power supply value	9 to 14 VDC
Current consumption	80 25

Physical

Physical dimensions	36 × 110 × 20 mm
Colour	Weiß
Material	Plastik
Mounting Type	Montaggio a superficie

Environmental

Vandal proof	No
Operating temperature	-35 to +66 °C
Environment	Drinnen
IP rating	IP54

En tant que société d'innovation, Kidde Global Solutions se réserve le droit de modifier les spécifications des produits sans préavis. Pour les dernières spécifications du produit, visitez le site web be.firesecurityproducts.com ou contactez votre représentant commercial.

Last updated on 12 November 2026 - 18:57