ATS1140

Ecrã tátil de 7" para a Adv Advanced/Everon

At a glance

The Advisor Advanced product family has a new addition: the ATS1140 graphical touchscreen. This device offers simple fingertip control of the security system with a 7-inch high-responsive touchscreen display that features easy-to-understand graphics. The ATS1140 is designed to perfectly complement other control units in the Advisor Advance security system family, ensuring a smooth user experience.

The ATS1140 boasts a modern design with a new graphical user interface that features icon-based and readable text. The display's contrast and the built-in buzzer's volume level can be adjusted via the configuration board. This device also comes with a simplified and intuitive graphical user interface, allowing users to easily navigate the programming, operational features, dashboard, system status, alarms, logs, and additional function keys.

Overall, the ATS1140 graphical touchscreen combines functionality and style to provide an efficient and user-friendly experience.



Built-in secure card reader

The ATS1140 is equipped with a Mifare Desfire EV1/EV2/EV3 card reader that is built-in. When the device is in secure mode, the data is encrypted from the card to the keypad and from the keypad to the Advisor Advanced control panel.

The ATS1140 can be used for arming/disarming the system with the PIN code, the card or a combination of both for enhanced security. It works with the multiple card badging solutions that are available in the Advisor Advanced product family.
Alarm system activation: a user can turn on the alarm system by badging their card three times within a 10-second interval.
Door access control: doors can be programmed for specific behaviors based on badging with the card. For example, with a single badge scan, granting seamless entry and exit without requiring a card, and a triple badge scan will promptly re-lock the door, providing enhanced convenience for the end user.

Quick access

The touch display menus are thoughtfully organized, featuring a clean and intuitive design that makes navigation a breeze. The single-touch operation eliminates the need for complex maneuvers, allowing for effortless interaction with the system. Whether you are an advanced tech user or a novice, you will find the touch display menus to be user-friendly and highly accessible.

Detalhes

- Design moderno e elegante
- Interface gráfica do utilizador simplificada e intuitiva
- Ecrã tátil a cores de 7"
- Possibilidade de acrescentar um logótipo personalizado no ecrã
- Teclas de função rapidamente acessíveis e programáveis
- Leitor seguro MIFARE Desfire EV1/EV2/EV3 incorporado
- LCD, campainha e luzes das teclas ajustáveis pelo utilizador
- Utilização de cartões seguros da série ATS145x ou cartões personalizados (exceto ATS1458)
- Interface de utilizador intuitiva e simplificada baseada em ícones
- Suporte multilinguagem
- Teclado virtual

ATS1140

Ecrã tátil de 7" para a Adv Advanced/Everon

Especificações técnicas

General

User interface	Przyciski kontaktronowe
Product line	Advisor Advanced, Everon
Status LEDs	1
Integrated reader	Zabezpieczone MIFARE
Language	Multi-language support
Supported Firmware	MR4.10 or later

System

Function keys	3
Supported card types	MIFARE® Classic UID, MIFARE® DESFire® EV1, MIFARE® DESFire® EV2, MIFARE® DESFire® EV3
Addressing type	Adresowanie programowe
Supported cable type	WCAT 52/54 ou equivalente

Communication

Communication type	Verdrahtet
Reading distance	Até 3 cm
Wiring	RS-485, 4-wire bus

Inputs/Outputs

Inputs	1
Input type	Request to Exit (NÃO)
Outputs	1
Output type	Colector aberto (OC), 100 mA máx., 15 VDC máx.

Electrical

Operating voltage	12.0 até 13.5 VDC (fornecido pelo painel)
Current consumption	330 mA a 13.7 VDC, 375mA a 12 VDC (max) 220 mA a 13.7 VDC, 250mA a 12 VDC (média) 70 mA a 13.7 VDC, 80 mA a 12 VDC (standby)

Physical

Physical dimensions	127 x 179 x 20 mm
Net weight	460 g
Colour	Weiß
Mounting type	Wandmontage
Material	ABS Plastik

Environmental

Operating temperature	0 a +50°C
Relative humidity	até 95% sem condensação
Environment	Drinnen

Regulatory

Certification	EN50131 Grad 3, F&P, FG, IMQ, INCERT, NFA2P, SBSC

Produtos compatíveis

Categoria	Referência	Descrição
Control Panel	ATS1700-MM	Painel de segurança Everon 1700, IP incorporado, EN G3, Web App, 8-48 zonas, 4 áreas, caixa metálica
Control Panel	ATS3700-MM	Painel de segurança Everon 3700, IP-onboard, EN grau 3, WebApp, 16 zonas base máx. 256 zonas, 16 áreas, caixa metálica média, multilíngue
Control Panel	ATS4700-LM	Everon ATS4700 Einbruchmeldezentrale, IP-Onboard, EN-Klasse 3, WebApp, 16 Onboard-MG, max. 1000 MG, 64 Bereiche, großes Metallgehäuse
Control Panel	ATS4700-MM	Sempre ligado. Sempre atento. Painel de segurança Everon 4700, IP-onboard, EN grau 3, WebApp, 16 zonas base máx. 1000 zonas, 64 áreas, caixa metálica média

Como empresa de inovação, a Kidde Global Solutions reserva o direito de alterar as especificações do produto sem aviso prévio. Para obter informações sobre as especificações mais recentes do produto, visite pt.firesecurityproducts.com online ou contate o departamento comercial.

Last updated on 12 November 2026 - 18:57